



- 1** - IN ADDITION TO EACH SOUNDBAR'S STANDARD DRIVERS, PHASE TECHNOLOGY'S SPATIAL FIELD EXPANDERS CREATE AN INCREDIBLY WIDE SOUNDSTAGE, CRUCIAL TO A REALISTIC SURROUND SOUND EXPERIENCE.
- 2** - OUR PROPRIETARY EVT (ENHANCED VOICE TECHNOLOGY) SWITCH ENGAGES SPECIFICALLY ENGINEERED CIRCUITRY THAT BOOSTS FREQUENCIES ASSOCIATED WITH HUMAN SPEECH, MAKING QUIET DIALOGUE EASY TO HEAR.
- 3** - THE TEATRO TSB3.0 SOUNDBAR PRODUCES THREE-WAY LEFT, CENTER, AND RIGHT CHANNEL AUDIO FROM A SINGLE CABINET MOUNTED DIRECTLY BELOW THE SCREEN.
- 4** - THE TEATRO V3.0 AND PC3.0 SOUNDBARS CAN BE FITTED WITH CUSTOM GRILLES TO MATCH THE WIDTH OF FLAT PANEL VIDEO SCREENS. CONTACT OUR SALES DEPARTMENT FOR DETAILS.



	TEATRO PC3.0	TEATRO V3.0	TSB3.0
DESCRIPTION	3-way LCR soundbar speaker with EVT™ intelligibility control	2-way LCR soundbar speaker with EVT™ intelligibility control	Ultra Thin LCR Soundbar Speaker with EVT™ Intelligibility control and SFE Spatial Field Expanders
TWEETER / MIDRANGE	3 x 1" Patented woven synthetic soft dome, 3 x 1.5" dome	3 x 1" Patented woven synthetic soft dome	3 x .75" Soft dome
WOOFER	3 x 5.25" Kevlar/glass fiber/RPF™ composite solid piston with NBR surround	3 x 5.25" VDT™ with NBR surround	3 x 3" Polypropylene woofers with rubber surround
ADDITIONAL DRIVERS	Spatial Field Expanders™, 2 x 1.5" patented woven synthetic soft dome	Spatial Field Expanders™, 2 x 1" patented woven synthetic soft dome	Spatial Field Expanders™, 2 x 1" aluminum wide range
FREQUENCY RESPONSE (+/- 3 DB)	52 Hz - 22 kHz	55 Hz - 22 kHz	75 Hz - 20 kHz
SENSITIVITY	89 dB	91 dB	90 dB
IMPEDANCE	4 Ω	4 Ω	8 Ω
RECOMMENDED AMPLIFIER POWER	15 - 150 W	15 - 120 W	15 - 100 W
DIMENSIONS	Height: 7" Width: 40" Depth: 4.5"	Height: 7" Width: 40" Depth: 4.5"	Height: 6.75" Width: 43" Depth: 1.5" (where it meets the television)

Gloss Black Satin Black

Standard color options for PC3.0.

Gloss Black

Standard color option for V3.0

Brushed Black

Standard color option for TSB3.0